

Desco Chemofluor 100-W



Acid and Caustic Service

Description:

A synthetic lubricant for glycols, strong acids and strong alkalis, refinery and petrochemical plant use.

Chemofluor is recommended for hard to hold applications such as glycols, solvents, strong acids and strong alkalis. It is also recommended for aromatic services.

Chemofluor white is available for applications where discoloration in a product stream may create a problem.

Service Recommendations:

Ammonia, alcohols, concentrated acids, hydrofluoric acid, ethylene glycol, ketones, other glycols, silicone oils and strong alkalis.

Typical Characteristics:

| | |
|-------------------|--------------------------------------|
| NLGI | 3-4 |
| ASTM penetration | |
| Bulk | 180 - 230 |
| Large stick | 80 - 100 |
| Small stick | 40 - 80 |
| Color | White |
| Temperature range | -30°F to +350°F (-34°C to +177°C) |

Packaging Information:

| Item No. | Unit Size | Quantity | Net Wt. | Ship Wt. |
|----------|---------------------------|------------|----------|----------|
| 100B-01 | "B" stick 3/8"x 1/2" | 72 per box | | .5 lbs. |
| 100C-01 | "C" stick 7/16"x 2-1/8" | 32 per box | | .5 lbs. |
| 100D-01 | "D" stick 1/2"x 2-1/4" | 28 per box | | .5 lbs. |
| 100G-01 | "G" stick 5/8"x 3-1/2" | 14 per box | | .5 lbs. |
| 100J -01 | "J" stick 1-3/8"x 8-1/2" | 16 per box | | 9 lbs. |
| 100K-01 | "K" stick 1-1/2"x 10-1/2" | 12 per box | | 10 lbs. |
| 100Z-01 | 14 oz. cartridges | 10 ctn. | | 12 lbs. |
| 1001-01 | 5 qt. | 1 each | 10 lbs. | 11 lbs. |
| 1002-01 | 3-1/2 gal. | 1 each | 20 lbs. | 23 lbs. |
| 1004-01 | 5 gal. | 1 each | 40 lbs. | 45 lbs. |
| 1010-01 | 16 gal. | 1 each | 120 lbs. | 130 lbs. |
| 1040-01 | 55 gal. | 1 each | 400 lbs. | 438 lbs. |