

Desco TFE-Seal 108

For Hard to Seal Valves



Description:

The ultimate sealant for damaged valves: TFE-Seal 108 was developed and tested by a group of valve repair specialists with over 20 years experience. This is the ultimate sealant of internally worn or damaged valves. If TFE-Seal 108 will not seal your valve nothing will short of a complete rebuild.

Formulated principally for: Sealant for worn or pitted valves. Can also be used as a sealant for stuffing boxes or as injectable packing.

Unique Features: Contains a 100% synthetic base fluid for excellent resistance to washout from hydrocarbons. Also contains chemically inert PTFE for ultimate sealing capabilities.

Typical Characteristics:

NLGI	2 1/2
Temperature range	-20°F to +550°F (-29°C to +287°C)

Packaging Information: Desco TFE-Seal 108

Item No.	Unit Size	Quantity	Net Wt.	Ship Wt.
080J-02	"J" sticks, 1-3/8" x 8-1/2"	16 per box		9 lbs.
0810-02	5 qt.	1 each	10 lbs.	11 lbs.

Caution:

TFE-Seal 108 has a low order of toxicity. However, it does contain TFE-fluorocarbon material and exposure to temperatures greater than +500°F (+260°C) will result in toxic gas being generated.

Caution:

May cause irritation with prolonged skin contact. Wash hands thoroughly after handling.

Caution: Do not use on Oxygen Lines