

Desco 600

Hydrocarbon Service



Description:

A superior lubricant formulated for resistance to hydrocarbons.

Our most popular lubricant for non-sour services. Contains 100% synthetic oils with a non-soap thickener. Tacky and resistant to washout in petroleum-based service.

Service Recommendations:

Aliphatic hydrocarbons, crude distillates, crude oil, diesel fuel, hydrocarbon liquids, kerosene, LPG, lubricating oils and natural gas.

Typical Characteristics:

NLGI	2
ASTM penetration	
Bulk	265 - 295
Large stick	80 - 130
Small stick	40 - 80
Base oil type	synthetic
Flashpoint	+450 ^o F (+232 ^o C) (COC)
Color	amber
Texture	tacky, smooth
Temperature range	-20 ^o F to +450 ^o F (-29 ^o C to +232 ^o C)
Shelf Life	guaranteed two years

Packaging Information:

Desco 600

Item No.	Unit Size	Quantity	Net Wt.	Ship Wt.
600B-01	"B" stick 3/8"x 1/2"	72 per box		.5 lbs.
600C-01	"C" stick 7/16"x 2-1/8"	32 per box		.5 lbs.
600D-01	"D" stick 1/2"x 2-1/4"	28 per box		.5 lbs.
600G-01	"G" stick 5/8"x 3-1/2"	14 per box		.5 lbs.
600J -01	"J" stick 1-3/8"x 8-1/2"	16 per box		9 lbs.
600K-01	"K" stick 1-1/2"x 10-1/2"	12 per box		10 lbs.
600Z-01	14 oz. cartridges	10 ctn.		12 lbs.
6001-01	5 qt.	1 each	10 lbs.	11 lbs.
6002-01	3-1/2 gal.	1 each	20 lbs.	23 lbs.
6004-01	5 gal.	1 each	40 lbs.	45 lbs.
6010-01	16 gal.	1 each	120 lbs.	130 lbs.
6040-01	55 gal.	1 each	400 lbs.	438 lbs.