

# Desco 622

## Hydrocarbon Service Low Temperature



### Description:

Desco 622 greatly expands the effective temperature range of synthetic valve lubricants while providing improved fuel and oil resistance.

Formulated with 100% synthetic base oil reinforced with a state-of-the-art additive package to provide superior sealing and lubricating properties.

### Service Recommendations:

Aliphatic hydrocarbons including, butane, crude distillates, fuels, oils, and propane. Also, dilute acids, dilute unleaded gasoline.

### Typical Characteristics:

NLGI	2
ASTM penetration	
Bulk	250-280
Large stick	80-100
Small stick	40-80
Base oil type	synthetic
Color	amber
Temperature range	-50 <sup>o</sup> F to +400 <sup>o</sup> F (-46 <sup>o</sup> C to +204 <sup>o</sup> C)

### Packaging Information:

#### Desco 622

Item No	Unit size	Quantity	Net Wt.	Ship Wt.
622B-01	"B" stick, 3 / 8" x 1- 1/2"	72 per box		.5 lbs.
622D-01	"D" stick, 1 / 2" x 2-1 / 4"	28 per box		.5 lbs.
622J-01	"J" stick, 1-3/8" x 8-1/2"	16 per box		9 lbs.
622K-01	"K" stick, 1-1/2 x 10-1/2"	12 per box		10 lbs.
622Z-01	14 oz. cartridge	10 per ctn.		12 lbs.
6221-01	5 qt.	1 each	10 lbs.	11 lbs.
6222-01	3-1/2 gal.	1 each	20 lbs.	23 lbs.
6224-01	5 gal.	1 each	40 lbs.	45 lbs.
6226-01	16 gal.	1 each	120 lbs.	130 lbs.
6229-01	55 gal.	1 each	400 lbs.	438 lbs.