

Desco 750

High Temperature Service



Description:

Formulated with 100% synthetic oils for hydrocarbon resistance at high temperature.

Desco 750 contains solid lubricants for effective lubrication at temperatures to +900°F.

Service recommendations below +450°F are similar to Desco 600.

Service Recommendations:

Aliphatic hydrocarbons, asphalt, hot oil, lubricating oils and steam.

Typical Characteristics:

| | |
|-------------------|--------------------------------------|
| NLGI | 3 |
| ASTM penetration | |
| Bulk | 220 - 250 |
| Large stick | 80 - 100 |
| Small stick | 40 - 80 |
| Color | dark amber |
| Temperature range | -20°F to +400°F (-29°C to +204°C) |

Packaging Information:

Desco 750

| Item No. | Unit Size | Quantity | Net Wt. | Ship Wt. |
|----------|---------------------------|------------|----------|----------|
| 750B-01 | "B" stick 3/8"x 1/2" | 72 per box | | .5 lbs. |
| 750C-01 | "C" stick 7/16"x 2-1/8" | 32 per box | | .5 lbs. |
| 750D-01 | "D" stick 1/2"x 2-1/4" | 28 per box | | .5 lbs. |
| 750G-01 | "G" stick 5/8"x 3-1/2" | 14 per box | | .5 lbs. |
| 750J-01 | "J" stick 1-3/8"x 8-1/2" | 16 per box | | 9 lbs. |
| 750K-01 | "K" stick 1-1/2"x 10-1/2" | 12 per box | | 10 lbs. |
| 750Z-01 | 14 oz. cartridges | 10 ctn. | | 12 lbs. |
| 7501-01 | 5 qt. | 1 each | 10 lbs. | 11 lbs. |
| 7502-01 | 3-1/2 gal. | 1 each | 20 lbs. | 23 lbs. |
| 7504-01 | 5 gal. | 1 each | 40 lbs. | 45 lbs. |
| 7510-01 | 16 gal. | 1 each | 120 lbs. | 130 lbs. |
| 7540-01 | 55 gal. | 1 each | 400 lbs. | 438 lbs. |