

Hanna-Seal # 55

Thread **On**

Thread Compound

Description:

A semi-curing thread compound manufactured for applications where a 100% seal is essential. An excellent sealant for line pipe carrying liquids or gases. Usable on threaded PVC, iron, steel, copper or fiberglass.

- * **Soft-set so threads can be broken out without galling or seizing.**
- * **Environmentally safe: contains no heavy metals.**
- * **Brushable to 0° F.**

Service recommendations:

Aqueous solutions including water, steam, ammonia, and alcohol. Dilute acids and caustics. Petroleum oils, vegetable oils, aliphatic hydrocarbon and solvents. CO₂, diesel, gasoline, mineral spirits, heating oils, LPG, natural gas, and other hydrocarbons.

Typical Characteristics:

Flash point (COC)	200° F (93° C)
Color	brown
Odor	slight
Temperature range (set)	-50° F to 400° F (-46° C to 204° C)
Usable temperature range	0° F to 150° F (-18° C to 66° C)
Pressure rating	to 10,000 psi.

Packaging Information:

Hanna-Seal #55

Item No.	Unit Size	Quantity	Net Wt.	Ship Wt.
532A-22	1/2 pt. b/t	12 per case	6 lbs.	10 lbs.
532B-22	1 pt. b/t	12 per case	12 lbs.	18 lbs.
5331-22	1 gal.	1 each	10 lbs.	11 lbs.

Caution: Do not use on Oxygen Lines