

325 Fiberglass



Thread Compound

Description:

325 Fiberglass Thread Compound is specially formulated for threaded fiberglass and PVC pipe. Provides for positive sealing integrity and resists water wash out, with ease of makeup and breakout. Contains TFE for critical sealing effectiveness and special additives to provide adequate lubrication for fiberglass pipe threads. Reduces breakout torque after extended service life.

Typical Characteristics:

NLGI	2
ASTM penetration unworked @ 77°F (25°C)	265 -295
Base grease	lithium-12- hydroxystearate
Base lubricating oil	
Viscosity, SUS @ 100°F (38°C)	900
Sulfur content, %	<0.3 %
Flashpoint	460°F (237°C)
Solids content	47.5 %
Color	dark gray
Texture	grainy
Brushable to	0°F (-18°C)
Temperature range	0°F to 450°F (-18°C to 232°C)

Packaging Information:

325 Fiberglass

Item No.	Unit Size	Quantity	Net Wt.	ShipWt.
3251-22	1 gal.	1 each	10 lbs.	11 lbs.
3253-22	3.5 gal.	1 each	35 lbs.	39 lbs.
3255-22	55 gal.	1 each	500 lbs.	535 lbs.

Contains No Lead

Caution: Do not use on Oxygen Lines