MATERIAL SAFETY DATA SHEET

Section 1. Chemic	al Product and Company Identification	Manufacturer	Manufacturer South Coast Products, Inc.				
Product Name	ThredOn L2M Special 20% Lead Base		20 Southbelt Industrial Dr.				
	Tool Joint Compound		Houston, TX 77	7047 USA			
Product Code	319						
Chemical Name	Not Applicable - Mixture	In Case of Emerge	ency 1-800-255-	-3924 or +813-248-0585			
<u>CAS #</u>	Mixture	Uses Thre	ad compound				
Section 2. Composition and Information on Hazardous Ingredients							
Name CAS #		<u>% by Weight</u>	<u>OSHA PEL</u>	ACGIH TLV			

Lead powder *

* Subject to the reporting requirements of Section 313 of Title III and of 40 CFR 372. ** Respiratory hazard—material in product is mixed into a grease and is very unlikely to become airborne under normal conditions.

15-25%

0.05 mg/m3 **

0.05 mg/m3 **

7439-92-1

COECIAL NOTE: MCDC date partains to the product or dispensed from the container. Adverse health effects would not be

SPECIAL NOTE: MSDS data pertains to the product as dispensed from the container. Adverse health effects would not be expected under normal conditions of use, so long as recommended safety precautions are practiced.

Section 3. Hazards Identification		Section 4. First Aid Measures			
Eye Contact	<u>t</u>	May cause tearing, redness, blurred vision, and irritation.	Flush eyes with clean water for at least 15 minutes. If irritation persists, call a physician.		
Skin Contac	<u>:t</u>	May cause drying of skin, irritation, and dermatitis.	Remove any contaminated clothing and wash skin with soap and water. If irritation occurs, call a physician.		
Skin Absorpt	<u>etion</u>	Absorption through intact skin not anticipated to be route of entry.	Accidental high pressure injection under skin requires immediate medical attention.		
Inhalation		Vapor pressure is very low. No significant hazard.	Not applicable.		
Ingestion		May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.	If victim is conscious, induce vomiting and give large quantities of water. Never give anything by mouth to an unconscious person. Get medical attention.		hing by mouth to an unconscious
Sensitization	<u>n</u>	Not a sensitizer under normal			
Chronic Effe	<u>ects</u>	conditions. May cause dermatitis. Overexposure to lead may cause anemia, weakness, abdominal pain, blood effects, and	Section 5. Fire and Exp Flash Point (method) Auto-Ignition Temp. Flammable Limits in Air		450°F (232°C) (COC) N/A <u>Iel:</u> N/A <u>uel:</u> N/A
<u>Carcinogeni</u>	<u>c Effects</u>	nerve and kidney damage. Lead and lead compounds: anticipated human carcinogens by NTP; possible	Combustion Products Explosion Hazards		Carbon monoxide, smoke, fumes. In the presence of mechanical impact or static discharge: no explosion risk.
Mutagenic E Teratogenic Reproductive	Effects	carcinogens by IARC. No data. Lead may cause damage to fetus. Lead may cause reduced fertility in men and women.	Fire Fighting Measures		Use foam, CO ₂ , dry chemical, water fog. Water can be used to keep containers cool and to flush spills away from fire exposure. Firefighters must wear self-contained breathing apparatus in enclosed areas.
		Section 6. Accident	al Release M	easures	
<u>Small Spill</u>	other suit	free product. Add sand, earth, or some table adsorbent. Dispose of material in nee with all state and local regulations.	<u>Large Spill</u> Take care to keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered sewers, watercourses, or extensive land areas.		
		Section 7. Hand	ling and Stor	age_	
<u>Storage</u>	container regulatio	cool dry area in original or equivalent r in accordance with all applicable ns. Do not expose to extreme heat or tore below 150°F.	<u>Handling</u> Wash thoroughly after handling. Do not get in eyes. Follow good hygiene and housekeeping practices. Use in ventilated areas.		
Section 8. Exposure Controls and Personal Protection Engineering Controls Use with adequate ventilation. Personal Protection Personal Protection Splash proof eye protection is advisable. Oil impervious gloves for prolonged or repeated skin contact.					

Appearance and Odo pH Boiling Point Melting Point Specific Gravity (H ₂ O: Water/Oil Distribution Coefficient	<u>r</u> Gray, grainy semi-solid, mi Not applicable No data No data = <u>1)</u> 1.3		essure nsity (Air=1) eshold on Rate	No data < 1 No data < 1 (ether = 1) Negligible	
Stability Conditions to Avoid	Stable. In	. Stability and Reactiv compatibilities azardous Decomposition	-	Strong oxidizers, acids. Carbon monoxide, smoke, fumes.	
Section 11. Toxicolo Routes of Entry Toxicological Data	ogical Information Eye, skin, ingestion. No data	Section 12. Ecolo Eco toxicity BOD5 and COD Biodegradation Pro Toxicity	-	<mark>ation</mark> No data No data No data	
Section 13. Disposa Waste Information	Il Considerations Dispose of waste according to federal, state, and local regulations.	hazar UN30 <u>IATA, IMO</u> Envir	ontainers ove rdous substan 077, 9, PGIII, F onmentally ha	<i>r 60 lbs net wt:</i> Environmentally ice, solid, n.o.s. (contains lead),	
<u>Hazardous Material Ir</u> Health Fire Reactivity Personal Protection	<u>Section 15.</u> iformation System (HMIS) (USA) 3* 1 0 B	Other Regulatory Info	<u>ormation</u>		
SARA Section 311/31	2 Hazard Classes: Lead: immedia	ate health, delayed heal	lth.		
SARA Section 313: In	ngredients subject to reporting requ	uirements: Lead, CAS#	7439-92-1.		
TSCA Inventory. All i	ngredients are listed or exempt.				
California Prop. 65: Ingredients listed: Lead (carcinogen, developmental toxicity, female reproductive toxicity, male reproductive toxicity).					
Canada DSL: All ingredients listed.					
WHMIS Classification: D2A, Very Toxic Material at =0.1%. WHMIS: This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. (Canada)					
required by the CPR. (Canada) Section 16. Other Information					
Date Revised For More Information	8/19/08	Prepared by	Sharon Stra	tman	
Important Notice		act for particular uses	are beyond o	vithout guarantee. Conditions of our control. Users should make their r products for their respective	