

QC 2000



General Purpose Protective Coating, Water Base

Description:

QC 2000 is a protective coating developed for use in dip coating of tubular goods and sucker rods. Other uses may be appropriate at user's discretion. This water base, non-combustible formula is excellent for dip tank operations. **QC 2000** is quick drying and forms a hard film with excellent mar and scuff resistance. It protects and preserves against rust and corrosion. **QC 2000** has excellent metal adhesion characteristics. It is not recommended for precision-fit machine parts as the coating is non removable except by severe abrasion. **QC 2000** is ready to use and may be applied by brush, dip or spray. If a spray application is used, spray equipment must be flushed with water immediately after use, as **QC 2000** once set, cannot be dissolved.

Typical Characteristics:

Coating vehicle	modified alkyd resin
Color	black
Odor	slight
Weight lbs./gal.	8.7
Water resistance	24 hours AD/4 hours pot pass ph 8.0-8.5
VOC, excluding water-gr./ltr.	22.6
Viscosity, #2 Zahn, sec.	20
Salt spray	
CRS-100 hours	1/6"
kB100-100 hours	1/6"

Packaging Information:

QC 2000

Item No.	Unit Size	Quantity	Net Wt.	Ship Wt.
2005-16	5 gal.	1 each	43 lbs.	47 lbs.
2055-16	55 gal.	1 each	478 lbs.	513 lbs.