

# Desco 625 Pak

## Wellhead Crossover Seals and P-Seals



### Description:

Contains a blend of 100% synthetic base oils that provides oil resistant performance from -80°F to +500°F.

The solid synthetic fibers and fillers provide a sure seal and are inert to most services.

Pumpable with a high pressure (10,000 psi.) lubrication hand gun.

### Service Recommendations:

Hydrocarbons, steam, water, sour gas and sour crude.

### Typical Characteristics:

ASTM penetration	25 - 40
Color	gray-green
Temperature range	-80°F to +500°F (-62°C to +260°C)

### Packaging Information:

#### Desco 625 Pak

Item No.	Unit Size	Quantity	Net Wt.	Ship Wt.
625B-12	"B" stick 3/8"x 1/2"	72 per box		.5 lbs.
625G 12	"G" stick 5/8"x 3-1/2"	14 per box		.5 lbs.
625J-12	"J" stick 1-3/8"x 8-1/2"	16 per box		10 lbs.
6242-12	3/8" x 1"stick	100 per box		20 lbs.
6211-12	1" x 1/8" ribbon, 1 gal.		10 lbs.	11 lbs.
6240-12	1" x 1/8" ribbon, 3- 1/2" gal		40 lbs	45 lbs..
6212-12	2" x 1/8" ribbon, 1 gal.		10 lbs	11 lbs.
6243-12	1" x 1/8" x 3-3/8"strip	100 per box		33 lbs.
6213-12	3/8" x 11"strip, 5 qt.		1 lbs.	2 lbs.
6210-12	3/8" x 1/2" coil, 5 gal.		50 lbs.	55 lbs.
6251-12	1 gal	1 each.	10 lbs.	14 lbs.
6254-12	5 gal.	1 each	40 lbs.	43 lbs.

### Caution:

Desco 625-Pak has a low order of toxicity. However, it does contain TFE-fluorocarbon material and exposure to temperatures greater than +500°F (+260°C) will result in toxic gas being generated.