

# Desco TFE Versi-Pak



## Packing Sealant

### Description:

A pumpable packing compound containing TFE-fluorocarbon particles blended into a synthetic binder.

**TFE Versi-Pak** is a highly versatile and durable self molding packing for use in stuffing boxes and for all types of valves, pumps and mechanical equipment.

It can be either pre-formed manually or pumped into place with a high pressure (10,000 psi.) grease gun.

**TFE Versi-Pak** is chemically stable and resistant to most chemicals over a wide pH range.

This is a permanent packing which can be added to and does not need to be replaced.

### Typical Characteristics:

ASTM penetration	
Bulk	40 - 80
Small stick	40 - 80
Large stick	40 - 80
Color	white
Temperature range	-20 <sup>o</sup> F to +500 <sup>o</sup> F (-29 <sup>o</sup> C to +260 <sup>o</sup> C)

### Packaging Information:

#### Desco TFE Versi-Pak

Item No.	Unit Size	Quantity	Net Wt.	Ship Wt.
100B-12	"B" stick 3/8"x 1/2"	72 per box		.5 lbs.
100C-12	"C" stick 7/16"x 2-1/8"	32 per box		.5 lbs.
100D-12	"D" stick 1/2"x 2-1/4"	28 per box		.5 lbs.
100G-12	"G" stick 5/8"x 3-1/2"	14 per box		.5 lbs.
100J-12	"J" stick 1-3/8"x 8-1/2"	16 per box		9 lbs.
100K-12	"K" stick 1-1/2"x 10-1/2"	12 per box		10 lbs.
1039-12	5/8"x 3" stick	140 per box		25 lbs.
1004-12	1/4" x 1" ribbon, 1 gal.		10 lbs.	11 lbs.
1011-12	1" x 1/8" x 3-1/4" strip		5 lbs.	6 lbs.
1003-12	5 qt.	1 each	5 lbs.	7 lbs.
1012-12	1 gal.	1 each	10 lbs.	14 lbs.
1015-12	3-1/2 gal.	1 each	25 lbs.	28 lbs.
1016-12	5 gal.	1 each	40 lbs.	43 lbs.

### Caution:

Desco TFE Versi-Pak has a low order of toxicity. However, it does contain TFE-fluorocarbon material and exposure to temperatures greater than +500<sup>o</sup>F (+260<sup>o</sup>C) will result in toxic gas being generated.