

Desco 111 (HS)

Hydrogen Sulfide Service



Description:

A synthetic lubricant for valves, swivel joints, pumps and flanges in service on sour gases and crudes.

Used worldwide in applications where hydrogen sulfide and carbon dioxide are present.

Desco 111 (HS) has high metal adhesion, corrosion resistance and is waterproof.

Service Recommendations:

Acid solutions, aliphatic hydrocarbons, diesel fuel, hydrogen sulfide, sour crude, sour gas, sulphonated oils and water.

Typical Characteristics:

NLGI	1
ASTM penetration	
Bulk	310 - 340
Large stick	80 - 100
Small stick	40 - 80
Color	black
Temperature range	-20 ^o F to +350 ^o F (-29 ^o C to +177 ^o C)

Packaging Information:

Desco 111 (HS)

Item No.	Unit Size	Quantity	Net Wt.	Ship Wt.
110B-01	"B" stick 3/8"x 1/2"	72 per box		.5 lbs.
110C-01	"C" stick 7/16"x 2-1/8"	32 per box		.5 lbs.
110D-01	"D" stick 1/2"x 2-1/4"	28 per box		.5 lbs.
110G-01	"G" stick 5/8"x 3-1/2"	14 per box		.5 lbs.
110J-01	"J" stick 1-3/8"x 8-1/2"	16 per box		9 lbs.
110K-01	"K" stick 1-1/2"x 10-1/2"	12 per box		10 lbs.
110Z-01	14 oz. cartridges	10 ctn.		12 lbs.
1100-01	5 qt.	1 each	5 lbs.	7 lbs.
1101-01	5 qt.	1 each	10 lbs.	11 lbs.
1102-01	3-1/2 gal.	1 each	20 lbs.	23 lbs.
1104-01	5 gal.	1 each	40 lbs.	45 lbs.
1110-01	16 gal.	1 each	120 lbs.	130 lbs.