

Desco 111-LT

Hydrogen Sulfide Service



Description:

Desco 111-LT is designed for use in valves under arctic conditions (to -75°F). **Desco 111-LT** is extremely resistant to hydrogen sulfide and will not mix with water, preventing freeze-up in the valve. Imparts good metal protection, provides lubrication and is waterproof.

Service Recommendations:

Diesel fuel, gas and well condensate, hydrogen sulfide, sour crude and standard crude.

Typical Characteristics:

NLGI	1
ASTM penetration worked	310 - 350
unworked	320 - 330
Base oil	100% synthetic
Flashpoint ASTM D -97	$+470^{\circ}\text{F}$ ($+243^{\circ}\text{C}$)
Base oil pour point / ASTM-97	-80°F (-62°C)
Color	black
Temperature range	-75°F to $+350^{\circ}\text{F}$ (-59°C to $+177^{\circ}\text{C}$)

Packaging Information:

Desco 111-LT

Item No.	Unit Size	Quantity	New Wt.	Ship Wt.
1141-01	14 oz. cartridge	10/ctn		12 lbs.
1142-01	5 qt.	1 each	10 lbs.	11 lbs.
1143-01	3-1/2 gal.	1 each	20 lbs.	23 lbs.
1144-01	5 gal.	1 each	40 lbs.	45 lbs.
1145-01	16 gal.	1 each	120 lbs.	130 lbs.
1146-01	55 gal.	1 each	400 lbs.	438 lbs.