

Desco 955

Premium Synthetic



Description:

An all-purpose hydrocarbon-resistant synthetic lubricant containing molybdenum disulfide.

Desco 955 is formulated with a solid lubricant (molybdenum disulfide) to provide lubrication to +600^oF. **Desco 955** is the standard lubricant used in gas pipelines. Service recommendations below +450^oF are similar to Desco 600.

Service Recommendations:

Aliphatic hydrocarbons, butane, fuel oil, asphalt, hot gases, hot oil, LPG and natural gas.

Typical Characteristics:

NLGI	4
ASTM penetration	
Bulk	185 - 215
Large stick	80 - 100
Small stick	40 - 80
Color	silver black
Temperature range	-40 ^o F to +600 ^o F (-40 ^o C to +316 ^o C)

Packaging Information: Desco 955

Item No.	Unit Size	Quantity	Net Wt.	Ship Wt.
950B-01	"B" stick 3/8"x 1/2"	72 per box		.5 lbs.
950C-01	"C" stick 7/16"x 2-1/8"	32 per box		.5 lbs.
950D-01	"D" stick 1/2"x 2-1/4"	28 per box		.5 lbs.
950G-01	"G" stick 5/8"x 3-1/2"	14 per box		.5 lbs.
950J -01	"J" stick 1-3/8"x 8-1/2"	16 per box		9 lbs.
950K-01	"K" stick 1-1/2"x 10-1/2"	12 per box		10 lbs.
950Z-01	14 oz. cartridges	10 ctn.		12 lbs.
9501-01	5 qt.	1 each	10 lbs.	11 lbs.
9502-01	3-1/2 gal.	1 each	20 lbs.	23 lbs.
9504-01	5 gal.	1 each	40 lbs.	45 lbs.
9510-01	16 gal.	1 each	120 lbs.	130 lbs.