

Desco

MAG-EP2 HT



Moly Anti-Seize and Extreme Pressure Lubricant

Description:

Desco MAG-EP2 is a general purpose non-melting lubricant with suspended molybdenum disulfide for special wear characteristics. It contains special additives for EP characteristics, corrosion inhibition and oxidation stability.

Greater anti-wear and anti-seize properties are enhanced by this special formulation, along with greater stability in the presence of acids and water.

Service Recommendations:

High temperature bearing applications, king pins, ball joints, gears, screws, kiln car bearings and hinges.

Typical Characteristics:

NLGI	2
ASTM penetration	265-295
Thickener	inorganic
Timken O K Load (lbs.)	45
ASTM Dropping point	>500 ^o F (>260 ^o C)
Pour point	-5 ^o F (-15 ^o C)
Color	bluish black
Temperature range	10 ^o F to +500 ^o F (-12 ^o C to +260 ^o C)

Packaging Information:

Desco Mag-EP2 HT

Item No.	Unit Size	Quantity	Net Wt.	Ship Wt.
040Z-04	14.5 oz. ctrg.	10 per ctn.	10 lbs.	11 lbs.
0403-04	5 gal.	1 each	35 lbs.	37 lbs.
0410-04	16 gal.	1 each	120 lbs.	130 lbs.
0440-04	55 gal.	1 each	400 lbs.	438 lbs.