

# Desco Red Bentone



## Hydrocarbon Grease

### Description:

**Desco Red Bentone Grease** offers the ultimate in general purpose lubricant with the added property of extreme pressure lubricity.

This grease is compounded from a blend of the finest mineral and synthetic oils coupled with an inorganic gelling agent.

**Desco Red Bentone Grease** offers additional protection to meet today's high performance requirements.

**Red Bentone Grease** is enhanced with the following proprietary formulation packages:

1. Oxidation Stabilization Package -- This keeps the oil and other organic components from becoming rancid, therefore increasing shelf life.
2. Corrosion Inhibitor Package -- To inhibit corrosion and rust.
3. Anti-Reactant Package -- This complex package keeps the various components from reacting with each other in an undesired way.
4. Anti-Leaching Package -- This helps to minimize oil separation.
5. EP Package -- This provides extreme pressure properties to the lubricant to prevent galling.

### Service recommendations:

King pin, ball joints, bearings, slides, gears, universal joints and screws.

### Typical Characteristics:

NLGI	2 to 2.5
ASTM Penetration	250-280
Thickener	inorganic
Timken OK load lbs.	45
ASTM Dropping point	+500°F (+260°C)
Pour point	-5°F (-15°C)
Color	red
Usable temperature range	0°F to +450°F (-18°C to +232°C)

### Packaging Information:

#### Desco Red Bentone

Item No.	Unit Size	Quantity	Net Wt.	Ship Wt.
020Z-04	14.5 oz. ctrg.	10 per case		12 lbs.
0203-04	5 gal.	1 each	35 lbs.	39 lbs.
0210-04	16 gal.	1 each	120 lbs.	130 lbs.
0240-04	55 gal.	1 each	400 lbs.	438 lbs.