

Desco TFE Polymel Pak

Injectable Packing



Description:

Desco TFE Polymel Pak is a pumpable packing designed for applications where a chemical resistant PTFE filled material is required.

Desco TFE-Polymel Pak is resistant to aliphatic hydrocarbons, alkalis, acids (including hydrofluoric) and aqueous solutions.

Service Recommendations:

Alkalis, butane, gasoline, hydrofluoric acid, natural gas and propane.

Typical Characteristics:

ASTM penetration	
Bulk and large stick	80 - 130
Small stick	50 - 70
Color	purple
Temperature range	-20 ^o F to +400 ^o F (-29 ^o C to +232 ^o C).

Packaging Information: Desco TFE Polymel Pak

Item No.	Unit Size	Quantity	Net Wt.	Ship Wt.
0203-12	"B" stick 3/8"x 1-1/2"	72 per box		.5 lbs.
0204-12	"C" stick 7/16"x 2-1/8"	32 per box		.5 lbs.
0210-12	"D" stick 1/2"x 2-1/4"	28 per box		.5 lbs.
0215-12	"J" stick 1-3/8"x 8-1/2"	16 per box		10 lbs.
0263-12	"K" stick 1-1/2"x 10-1/2"	12 per box		10 lbs.
0230-12	5 qt.	1 each	10 lbs.	11 lbs.
0232-12	5 gal.	1 each	40 lbs.	43 lbs.

Caution:

Desco TFE Polymel-Pak has a low order of toxicity. However, it does contain TFE-fluorocarbon material and exposure to temperatures greater than +500^oF (+260^oC) will result in toxic gas being generated.